

LumiDawg IP65 UV Flood

LumiDawg UV Flood is an IP65 Rated UV PAR style fitting. The output is true UV at 365 nanometer wavelength. These units will whites and Neon colours glow. Diecast aluminum housing, Split Yoke and Stipple lens.



Physical

Size of Unit	251 x 225 x 308mm
Item Weight	6.5kg
Quantity in Case	???

Electrical

Rated Power	100W
Input Power	100-240v AC 50/60Hz
Power Connection	PowerCON TruCon 1 input and output

Mounting Options

Hanging Type	Trigger clamp,
Freestanding	Yes – with split yoke
Expo LX	No

Optical

Light Source	1 x High Power COB UV 100W
Beam Angle	50 degrees
Colour	365nm Wavelength

Control

Control Method	DMX, RDM,
DMX Mode	1/2 channel
DMX Channel List	See attached links
DMX Connection Types	5pin DMX,

Environmental

IP Rating	IP65
Cooling	passive cooling
Max Operating Temperature	10-40°

Accessories Included

- 1 x Trigger clamp
- 1 x Safety chain
- 1 x Power lead

GOBO

Not available on this unit

Colour

365 nanometer Wavelength

Information Links

Manual Link [LumiDawg UV Flood Manual](#)

